THE QUICKEST WAY TO TRAVEL. ELITE TRAVEL **GO-GO ELITE TRAVELLER®** The Go-Go Elite Traveller®'s compact design allows it to easily manoeuver in tight spaces while providing stable outdoor performance. Take the guesswork out of travel with simple, one hand Feather-touch disassembly. Go where you want to go, easily, with the Go-Go Elite Traveller.

(Tel) 03 9706 4611 • (Fax) 03 9706 4622 • www.pridemobility.com

Mobility Products Australia Pty. Ltd.

Go-Go Elite Traveller®	3-wheel	4-wheel
Weight capacity:	125 kg (275 lbs.)	125 kg (275 lbs.)
Maximum speed ² :	Up to 7 km/h (4.25 mph)	Up to 7 km/h (4.25 mph)
Ground clearance ¹ :	6.5 cm (2.625") at midframe	6.35 cm (2.5") at midframe
Turning radius¹:	82.5 cm (32.5")	110 cm (43.25")
Overall length ¹ :	92.75 cm (36.5")	101 cm (39.75")
Overall width ¹ :	49 cm (19.25")	48.5 cm (19.125")
Tyres:		
Front:	5 cm x 20 cm (2" x 8") solid	5 cm x 18 cm (2" x 7") solid
Rear:	6.35 cm x 20 cm (2.5" x 8") solid	6.35 cm x 20 cm (2.5" x 8") solic
Anti-tips:	Rear	Rear
Transport weight:		
Total weight w/o battery pack:	34 kg (75 lbs.)	35.5 kg (78.5 lbs.)
Heaviest piece when disassembled:	12.75 kg (28 lbs.) (front section)	15 kg (33.5 lbs.) (front section)
Drive System:	24-volt DC motor, sealed mini-transaxle	
Dual Braking System:	Electronic, regenerative, and electromechanical	
Standard seating:	Foldable, compact, vinyl-covered molded plastic	
Battery Charger:	Off-board, 2-amp	
Per-charge range ² :	Up to 22.5 km (14 miles) (3 or 4-wheel w/ 2 x 18 AH) standard	
Battery Requirements ³ :	Two 12-volt, deep cycle (standard) Size: 2 x 18 AH Weight: 18 AH: 15 kg (33 lbs.) battery pack	

Standard Colours:







3 sets of colours with every scooter!

Features

- Feather-touch disassembly permits simple frame separation with only one hand
- Easy drive tiller with wraparound handles
- Pride's exclusive black non-scuffing tyres with tri-spoke wheels
- Auto-connecting front to rear cable
- Includes 3 sets of easily changeable coloured panels in 3 exciting colors - Red, Blue and Silver
- Front frame-mounted seat post offers maximum stability
 - All-new frame design easily disassembles into 5 super lightweight pieces for convenient transport and storage
 - Modular design for easy serviceability
 - Microprocessor-based controller offers optimal power management and added safety features
 - Standard front tiller-mounted basket included
- Removable deck basket for additional storage (4-wheel only)
- Convenient off-board dual voltage charger can charge battery pack on-board or off-board
- 2 x 18 AH battery pack for maximum range per charge (standard)

Options

- Cup holder
- 2 x 12 AH battery pack for maximum portability



Feather-touch disassembly

- ¹ Due to manufacturing tolerances and continued product improvement, this specification is subject to a variance of +/- 3%.
- ² Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure.
- ³ Battery weight may vary based on manufacturer.



The information contained herein is correct at the time of publication; due to the manufacturers commitment to constant improvement and development, they reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.

21 Healey Rd., Dandenong, Victoria 3175 (Tel) 03 9706 4611 • (Fax) 03 9706 4622 • www.pridemobility.com

