

Pathrider™ 130 XL

OUTSTANDING OUTDOOR
PERFORMANCE WITH
LUXURIOUS FEATURES

PATHRIDER™ 130 XL

The **Pathrider 130 XL** features a powerful drive train and large 33 cm (13") wheels to handle rugged outdoor terrain. Luxury touches like a wraparound easy drive tiller, low profile non-marking tyres and LED kerb light blend seamlessly giving the Pathrider 130 XL a sleek, sporty style.



Pride[®]
Mobility Products
Australia Pty. Ltd.
— LIVE YOUR BEST —

(Tel) 03 9706 4611 • (Fax) 03 9706 4622 • www.pridemobility.com

Pathrider™ 130 XL

Weight capacity:	181 kg (400 lbs.)
Maximum speed ¹ :	Up to 12 km/h (7.45 mph)
Ground clearance ² :	11.76 cm (4.63")
Turning radius:	169.5 cm (66.75") right/ 172 cm (67.75") left
Overall length ² :	135.25 cm (53.25")
Overall width ² :	64 cm (25.25")
Front tyres:	10 cm x 33 cm (4" x 13") solid
Rear tyres:	10 cm x 33 cm (4" x 13") solid
Seat-to-deck:	46 cm (18")
Seat-to-ground:	63 cm – 67 cm (25" – 26")
Suspension:	Front & rear
Range per charge ^{1,4} :	Up to 34 km (21.13 miles) (with 75 AH batteries)
Maximum obstacle climbing ability:	2.5 cm (1")
Total Weight Without Batteries:	97.5 kg (215 lbs.)
Heaviest piece when disassembled:	43 kg (95 lbs.) (front section)
Standard seating:	Type: Deluxe Captains seat Weight: N/A Material: Black Vinyl Dimensions: width – 49.5 cm (19.5") (overall width) depth – 44.5 cm (17.5") (effective depth)
Drive System:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual Braking System:	Electronic, regenerative, and electromechanical
Battery Requirements ³ :	Two 12-volt, deep cycle Size: 55 AH (standard) 70 AH (optional) Weight: 55 AH: 17.24 kg (38 lbs.) each 70 AH: 24.27 kg (53.5 lbs.) each;
Battery Charger:	5-amp, off-board (w/ 55 amp batteries)
Warranty:	2-year limited

Colours:



Candy Apple
Red



Mercury
Silver

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition.

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³ AGM or Gel-Cell type required.

⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance test conducted at maximum weight capacity.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.

Features

- Large 33 cm (13") solid tyres for excellent outdoor performance
- Full lighting package including directional signals and angle-adjustable, dual bulb lower headlight
- Easy drive tiller with wraparound handles
- Front basket standard
- Easily accessible tie down points (for transport of unoccupied scooter)
- Rear view mirror standard

Options

- Rear basket
- Safety flag
- Walker holder
- Durable weather cover